

## DO600L DO Meter



### GENERAL FEATURES

- Color High contrast LCD touchscreen, 7.0 inches.
- Intelligent operation system provides features including user management, calibration management, method management, data management and etc.
- Multi-reading feature allows auto-read, timed-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Data Storage 1000 sets for each parameter (GLP-compliant).
- Data analysis feature helps user review, compare and recalculate results.
- Support for USB or RS-232 communication.
- Reset feature automatically resumes all settings back to factory default options.
- IP54 waterproof.
- Support for air-saturated water or zero oxygen calibration.
- Auto barometric pressure compensation.
- Manual Salinity Factor Correction.
- Selectable pressure unit, including kPa, mbar, Torr, Atm.

Model		DO-600L
Parameters		DO/Temp(DO Saturation).
Dissolved Oxygen Concentration	Sensor Type	Polarographic
	Range	0.00 to 99.99 mg/L
	Resolution	0.01 mg/L
	Accuracy	± 0.1 mg/L
	Calibration Reminder	Yes
	Calibration Points	Air-saturated water or zero point
	Barometric Compensation	Yes
	Manual Salinity Factor Correction	Yes
DO Saturation	Range	(0.0 to 600)%
	Resolution	0.10%
	Accuracy	± 10.0%
Temperature	Range	-5 to 130 °C
	Unit	°C
	Resolution	0.1
	Accuracy	± 0.1
Measurement	Reading Mode	Auto Read (Fast, Medium, Slow), Timed, Continuous
	Reading Prompts	Reading, Stable, Locked
	Temp. Compensation	ATC, MTC
Data management	Data Storage	1000 Groups
	GLP Features	Yes
	Log Management	Yes
Inputs	DO with Temp. Probe	6-pin Mini-DIN
Outputs	USB, RS 232	USB 2.0 flash memory device, printer, PC
Display options	Backlight	Yes
	Auto Shutdown	1~60 min, off
	IP Rating	IP54
	Date and Time	Yes
General	Power	AC Adapter, 100-240V AC input, DC24V output
	Dimensions	280 × 280 × 130 mm
	Weight	2500g (5.51 lb)